

Technical Data Sheet

Kunshan EMF Industrial Co., Ltd.	+86 512 571 131 82 Tel
91 Xinpu Road, Kunshan City	+86 512 571 131 83 Fax
P.R.China. 215337	+86 138 626 007 66 Mobile
www.emfcn.com	sales@emfcn.com e-Mail

FLOATING LIFELINE FOR LIFEBOUY

REFERENCE STANDARD

RESOLUTION MSC.48 (66)

Buoyant lifelines required by regulation 111/7.12 shall:

1. be non-kinking,
2. have a diameter of not less than 8 mm. and
3. have a breaking strength of not less than 5 kN.

PARTICULARS

- Description of Goods: Floating Lifeline for Lifebuoys
- Model: HLW8-B
- Rope Material: UV resistant Polypropylene fiber (PP), so floating on water
- Rope Type: Braided and Non-Kinking (8 strands type on request).
- Rope Color: Safety Orange
- Rope Size: Diam. 8 mm x 30 Mtrs.
- Application: To be attached to a lifebuoy for MOB incidents and for several other marine uses.

Features:

- The vibrant color ensures high visibility for quick and efficient lifesaving.
- The rope stays lightweight and buoyant remains on the water's surface for easy retrieval and is reliable and durable for critical situations.
- Maintains integrity and performance over time.



Important: This datasheet is subjected to change without notice.